

staticworx® Reference

Staticworx StatBond Adhesive – Material Safety Data Sheet

SECTION 1: IDENTITY

TRADE NAME AND SYNONYMS:
Staticworx STATBOND Adhesive

CHEMICAL NAME AND SYNONYMS:
Waterborne acrylic adhesive

CHEMICAL FAMILY: Acrylic

MOLECULAR FORMULA: Not applicable

PRODUCT DESCRIPTION:
Waterborne acrylic dispersion adhesive

Provider: StaticWorx
PO Box 590069
Newton, MA 02459

Telephone Number for Information: (617) 923-2000
Emergency Phone Number : (800) 255-3924

SECTION 2: HAZARDOUS INGREDIENTS

Chemical	CAS Number	TLV	TLV-TWA	PEL-STEL	%
Titanium dioxide#13463-67-7	...15 mg/M ³	...15 mg/M ³	...10 mg/M ³	..10-15

SECTION 3: HAZARDOUS IDENTIFICATIONS

EMERGENCY OVERVIEW: May cause eye irritation. May cause respiratory irritation. May cause central nervous system depression. Smoking and/or consumption of alcoholic beverages may increase toxic effects of this material.

POTENTIAL HEALTH EFFECTS:

EYE CONTACT: May cause irritation. May damage eyes.

SKIN CONTACT: Prolonged exposure may cause skin irritation May cause drying or flaking of skin.

INGESTION: Ingestion may cause injury to intestinal tract, liver, kidneys, stomach, throat, lungs, mouth and mucous membranes. Harmful or fatal if swallowed. Do not ingest.

INHALATION: Prolonged overexposure may cause respiratory tract irritation.

SECTION 4: FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

SKIN: Wash with soap and water. Get medical attention if irritation develops or persists. Immediately remove contaminated clothing.

INGESTION: If swallowed, seek medical attention immediately. Do not induce vomiting. Can enter lungs and cause damage.

INHALATION: Remove to fresh air. Restore breathing if necessary. Get medical attention.

DO NOT LEAVE VICTIM UNATTENDED.

SECTION 5: FIRE FIGHTING MEASURES AND FIRE HAZARDS

OSHA FLAMMABILITY CLASS: IIIB

FLASHPOINT: > 200°F, > 93°C (Setaflash method)

LOWER EXPLOSIVE LIMIT: Not available.

UPPER EXPLOSIVE LIMIT: Not available.

GENERAL HAZARD: Toxic gases will form upon combustion. Closed containers may explode when exposed to extreme heat. Vapours are heavier than air and may travel a considerable distance.

FIRE FIGHTING EQUIPMENT: Respiratory and eye protection required for firefighting personnel. Full protective equipment and a self-contained breathing apparatus (SCBA) should be used in all indoor fires and any large outdoor fires.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide, carbon dioxide, smoke and fumes, hydrocarbon fragments.

(continued on next page)

staticworx® Reference

Staticworx StatBond Adhesive – Material Safety Data Sheet (cont.)

SECTION 6: ACCIDENTAL RELEASE MEASURES (SPILLS OR LEAKS)

GENERAL INSTRUCTIONS: Isolate the danger area and keep out unauthorized personnel. Stop spill if it can be done with minimal risk. Wear appropriate protective equipment including respiratory protection as conditions warrant (see section 8). Prevent additional discharge of material. Notify the appropriate authorities immediately. Contain spilled liquid with sand, earth or other non-combustible inert absorbent material. Prevent run-off from entering storm sewers, ditches or waterways. Transfer absorbed waste material into properly identified drums. Treat waste material with same precautions as the adhesive.

Do not use solvent or flammable liquid to help clean up an accidental release.

Release to the environment may be reportable under environmental regulations.

SECTION 7: HANDLING AND STORAGE

HANDLING: Do not enter confined spaces such as tanks without following proper entry procedures as described in OSHA regulations at 29 CFR 1910.146. Do not breathe vapours. The use of respiratory protection is recommended when airborne concentrations of vapour exceed exposure guidelines. Wash thoroughly after handling. Do not wear contaminated clothing or shoes. Wear appropriate protective gloves and clothing to prevent prolonged or repeated skin contact. Avoid contact with eyes.

STORAGE: Keep containers tightly closed. Use and store this material in a cool, dry, well-ventilated area away from heat, direct sunlight, hot metal surfaces, and all sources of ignition. Store only in approved containers. Protect containers against physical damage. Indoor storage should meet OSHA standards and appropriate fire codes.

EMPTY CONTAINERS: May contain liquid and vapour residue and may be dangerous. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. "Empty" drums should be completely drained, properly bunged, and promptly shipped

to the supplier or a drum reconditioner. All containers should be disposed of in accordance with governmental regulations.

Wash with soap and water before eating, drinking, smoking or using toilet facilities.

Consult NFPA and OSHA codes.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

RESPIRATORY PROTECTION: Specific respiratory protection is not necessary when the adhesive is used as recommended. If in doubt, seek the advice of an industrial hygienist or safety professional for appropriate respiratory equipment.

SKIN PROTECTION: The use of gloves impermeable to the specific material handled is advised to prevent prolonged or repeated skin contact. Where splashing is likely to occur, aprons impermeable to the specific material may be worn. Refer to the glove and protective clothing manufacturer's selection guide for appropriate material.

EYE PROTECTION: Approved chemical splash goggles should be worn to safeguard against potential eye contact, irritation or injury. Where splashing is likely to occur, hard hats and face shields may be used to provide additional protection. Eye wash facilities should be available in the work area.

ENGINEERING CONTROLS: The use of local exhaust ventilation is recommended. Provide mechanical ventilation of confined spaces.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE AND ODOUR: Grey paste with low odour

SPECIFIC GRAVITY: 1.02 (68°F – 20°C)

pH: 6.5-8.5

BOILING POINT: Approx. 212°F, 100°C

(continued on next page)

staticworx® Reference

Staticworx StatBond Adhesive – Material Safety Data Sheet (cont.)

FREEZING POINT: Approx. 32°F, 0°C

SOLUBILITY IN WATER: Soluble

% SOLIDS (BY WEIGHT): 71 ± 2%

% VOLATILE (BY WEIGHT): 29 ± 2%

VAPOUR PRESSURE (MM OF MERCURY): Same as water

VAPOUR DENSITY (AIR = 1): Heavier than air

EVAPORATION RATE (BUTYL ACETATE = 1):
Slower than butyl acetate

EVAPORATION RATE (ETHYL ETHER = 1):
Slower than ethyl ether

SECTION 10: STABILITY AND REACTIVITY

CHEMICAL STABILITY: Keep away from flames and spark producing equipment. Not dangerously unstable.

INCOMPATIBLE MATERIALS: Strong oxidizing agents, strong reducing agents, acids, bases, or unstable chemicals, chloroform, nitric compounds, peroxides, sulfur dichloride, strong alkalis.

HAZARDOUS DECOMPOSITION PRODUCTS: Hazardous decomposition is unlikely to occur, but under fire or extreme heat conditions, carbon monoxide, carbon dioxide, smoke and fumes, and hydrocarbon fragments can be released.

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

MATERIAL: SKIN (Dermal LD50): INGESTION (Oral LD50):

Titanium dioxide.....>10 g/M3 (Rat)>24 g/kg Oral/Rat

CHRONIC: Liver and kidney damage FROM OVEREXPOSURE.

May cause central nervous system depression.

CHRONIC / CARCINOGENICITY (CANCER CAUSING):

IARC: Group 2B - Possibly carcinogenic to humans. IARC's Monograph No. 93 reports there is sufficient evidence of carcinogenicity in experimental rats exposed to titanium dioxide but inadequate evidence for carcinogenicity in humans and has assigned a Group 2B rating. In addition, the IARC summary concludes, "No significant exposure to titanium dioxide is thought to occur during the use of products in which titanium is bound to other materials, such as paint."

OSHA: Not suspected as a human carcinogen.

NTP: Not suspected as a human carcinogen.

OTHER: This product contains the following chemicals known to the state of California (Proposition 65) to cause cancer or reproductive toxicity: None known.

OTHER: None known.

SECTION 12: ECOLOGICAL INFORMATION

No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Incinerate at an EPA approved facility or dispose of in accordance with all federal, state/provincial and local regulations.

See Section 2 of this MSDS for hazardous ingredients.

PROPER WASTE DISPOSAL IS THE RESPONSIBILITY OF THE OWNER OF THE WASTE!

Call Staticworx if additional information is necessary.

(continued on next page)

staticworx® Reference

Staticworx StatBond Adhesive – Material Safety Data Sheet (cont.)

SECTION 14: TRANSPORTATION INFORMATION

D.O.T. / T.D.G.: NOT REGULATED

All packaged material must be labeled in accordance with DOT and OSHA standards.

SECTION 15 – REGULATORY INFORMATION

OSHA: Hazardous material by definition of hazard communication standard (29CFR 1910.1200).

SECTION 313: This product contains the following substances subject to the reporting requirements of Section 313 of TITLE III of Superfund Amendments and Reauthorization Act of 1986 and CFR Part 372: None known.

V.O.C.: <0.1 Lbs/Gal. (SCAQMD Rule 1168)
<1 G/L

VHAP: 0 lb/lb solids

HMIS RATINGS:

HAZARDOUS - NO

HEALTH = 1

FLAMMABILITY = 1

REACTIVITY = 0

PERSONAL PROTECTION = Depends on application and ventilation.

TSCA = Components of this product are listed on the TSCA inventory.

(4 = Most Hazardous)

WHMIS INFORMATION:

Class D, Division 2, Subdivision A

SECTION 16:

OTHER INFORMATION

All employees or contractors, etc., who use this product must have access to this Material Safety Data Sheet.

SECTION 17: DEFINITIONS

ACGIH : American Conference of Governmental Industrial Hygienists.

ASPIRATION HAZARD: The danger of drawing material into the lungs, leading to an inflammatory response that can be fatal.

CFR: Code of Federal Regulations (U.S.). A collection of regulations established by law.

CARCINOGEN: A material that either causes cancer in humans, or is considered capable of causing cancer in humans.

COMBUSTIBLE: A term used to classify certain materials with low flash points that ignite easily. For OSHA it has a flash point greater than 100°F (38°C) but below 200°F (93°C).

DOT: U.S. Dept. of Transportation.

FLAMMABLE: A material that gives off vapours that readily ignite at room temperatures. OSHA defines flammable as a material with a flash point less than 100°F (38°C).

FLASH POINT: The lowest point at which a liquid gives off sufficient vapour to form an ignitable mixture with air.

HAZARDOUS: Any substance or mixture of substances having properties capable of producing adverse effects on the health or safety of a human.

IARC: International Agency for Research on Cancer.

IRRITANT: A substance capable of causing an inflammatory effect on living tissue by chemical action at the site of contact.

LD50: Lethal Dose 50. The single dose of a substance that causes death of 50% of an animal population from exposure to the substance from any route other than inhalation.

(continued on next page)

staticworx® Reference

Staticworx StatBond Adhesive – Material Safety Data Sheet (cont.)

LEL: Lower Explosive Limit. The lowest concentration of vapour that burns or explodes when an ignition source is present at ambient temperatures.

LFL: Lower Flammable Limit. See L.E.L.

MSHA: Mine Safety and Health Administration (U.S.).

NFPA: National Fire Protection Association (U.S.).

NIOSH: National Institute of Occupational Safety and Health (U.S.).

NTP: National Toxicology Program (U.S.).

OECD: Organisation for Economic Co-operation and Development.

OSHA: The Occupational Safety and Health Administration (U.S.).

PEL-STEL: Permissible Exposure Limit, Short Term Exposure Limit.

SCBA: Self-contained breathing apparatus.

SYSTEMIC TOXICITY: Adverse effects induced by a substance which affects the body in a general manner rather than locally.

TDG: Transportation of Dangerous Goods (Canada).

TLV-TWA: Threshold Limit Value, Time Weighted Average.

TSCA: Toxic Substance Control Act.

TOXIC: Any chemical or material that has evidence of an acute or chronic health hazard and is listed in the NIOSH Registry of Toxic Effects of Chemical Substances.

VHAP: Volatile Hazardous Air Pollutant

V.O.C.: Volatile Organic Compound.

WHMIS: Workplace Hazardous Materials Information System (Canada).